



G3™ Electric Lubrication Pump

For Series Progressive and Injector-based Systems



PROVEN QUALITY. LEADING TECHNOLOGY.

If you're not using **Graco G3** pumps, you're not **maximizing** your **profits**.



Rigorously tested to pass Graco specifications and earn these approvals—
we'd love to have yours, too.



Contact us today!

To receive product information or to speak with a Graco representative, call 800-533-9655 or for a complete list of G3 Pumps and configurations visit us online at www.graco.com—keywords: G3 Pump Selection Guide (340706).

Versatile Design Helps Solve Today's Lubrication Challenges.



Why G3 is Better

Two in One Design Does More!

G3's flexible design works with injector-based and series progressive systems. A cost-effective pump designed to serve multiple markets and applications.

Options that fit your business

Three controllers to choose from with multiple zone and feedback options. Includes one adjustable pump element—standard, plus room for two more. Multiple reservoir choices and more! The ultimate in flexibility—for a high value, custom fit on your application.

Built-in Tools To Help you Succeed

Work faster and smarter with Graco's exclusive Data Management System (DMS™). Find out exactly how your lubrication system is performing and how well it's lubricated. Tracks history, provides data protection, upload or download data using a simple USB flash drive.

World Wide Support with Experienced Professionals

Graco wants to help you become more successful. Our staff of professional engineers, designers, field experts and customer service representatives are at your service. We invite you to call on us to partner in your next project.

Extend machinery life, reduce operating costs and increase productivity with a Graco G3 today!

Take a look inside— we think you'll like what you see

Designed from the inside-out for longer lasting performance and reliability. G3 meets changing temperatures, challenging installation requirements and changing grease types head-on. Graco's newest electric pump delivers high performance results in real world application conditions.




Advanced Flow Dynamics

Specially contoured base funnels grease directly to the pump inlet to significantly reduce stagnant flow areas where soaps and grease fillers can accumulate.



Adjustable Stroke Pump

With G3, adjustability comes standard! Eliminate the need to purchase additional fixed output elements or high-priced adjustable elements.



Load Minimizing Drive

Each G3 piston pump element is offset from the main motor shaft resulting in less stress on the motor and internal components.

Versatile, Hard-working Pump

Designed for You to Succeed

Two Reservoir Types

Stirring paddle with wiper arm to keep material from separating. Follower plate available for extreme angle installations

Multiple Reservoir Sizes

Choice of 2, 4, 8, 12 or 16 liter U.V. resistant, high-impact reservoirs for oil and grease to meet the needs of your equipment

Power Choices

Connect to DC (12 or 24v) and AC (90-240v) power sources with CPC or DIN-style connectors for easy, no hassle installations

Three Pump Elements

G3 comes standard with one adjustable pump element installed—add up to two more for higher output on large projects

Vent Valve Output

Combine Max controller with a vent valve for injector-based systems

Multiple Cycle and Pressure Inputs

Mix and match up to three cycle and pressure switches for custom installations and feedback

Three Controller Options

Choose from Standard, Pro and Max controller options—buy only what you need for your application

Machine Count Input

Machine count input to manage equipment with unpredictable lubrication requirements



Data Management System (DMS)

- Simple data transfer to your PC via USB flash drive for further analysis using Excel® or Notepad®
- Provides performance history for lube system events, such as cycle detection, error logs and allows a quick check of lubrication performance to meet your system requirements
- Preferred lube cycle program can be stored and transferred to other G3 pumps in your fleet for quick and accurate repeatability
- Provides you the comfort and security in knowing your pump is being properly maintained and your lube system is protecting your valuable asset

Control for Your Business

Standard, Pro and Max

Choose the level of control you need for your series progressive or injector based applications.



G3 Standard

- No internal controller—use with separate or existing machine control for a low cost solution
- Capable of sending a low level signal to your external controller or PLC



G3 Pro

- Built-in controller with selectable pump on/pump off timer
- Low level indicator provides low warning and shut-down alarm
- Manual run initiates lube cycle on-demand (remote option also available)
- Password protection safeguards settings
- Pre-lube function can initiate lube cycle on start-up



G3 Max

- Built-in controller with selectable pump on/pump off timer
- Low level indicator provides low warning and shut-down alarm
- Manual run initiates lube cycle on-demand (remote option also available)
- Password protection safeguards
- Pre-lube function can initiate lube cycle on start-up
- Up to three pressure or cycle switch inputs to ensure proper lubrication cycles
- Mix/match cycle and pressure switches for custom installations and feedback
- Machine count input—ideally suited for inconsistently used equipment
- Fault indication to external alarms
- Optional Data Management System™ (DMS)

Check out the full-featured G3 Max

- 1 Easy-to-read LED display
- 2 Clearly identified pump on/off indication
- 3 Monitoring of up to three independent zones
- 4 Programmable machine count feature
- 5 Alarm signal of lube system shutdown
- 6 Warning signal prior to lube system shutdown
- 7 Low level indication
- 8 Password protected access to control
- 9 Pre-lube capability
- 10 Easy-to-use navigation keys



Tech Specs

Max Pressure 5100 psi (352 bar)
Power 12 VDC, 24 VDC, 90-240 VAC
Operating Temperature -13 to 158° F (-25 to 70° C)
Reservoir Size..... 2, 4, 8, 12, or 16 liter
Adjustable Pump Output Per Element Per Minute....
0.12 in³, 0.18 in³, 0.25 in³ (2 cm³, 3 cm³, 4 cm³)
Lube Type Oil or Grease, up to NLGI #2
Certifications/Ratings.....CE, ETL*, IP69K
*Conforms to UL 73, certified to CSA 22.2 No. 68-09
Instruction Manual 3A0414



ABOUT GRACO

PROVEN QUALITY. LEADING TECHNOLOGY.

Founded in 1926, Graco is a world leader in fluid handling systems and components. Graco products move, measure, control, dispense and apply a wide range of fluids and viscous materials used in vehicle lubrication, commercial and industrial settings.

The company's success is based on its unwavering commitment to technical excellence, world-class manufacturing and unparalleled customer service. Working closely with qualified distributors, Graco offers systems, products and technology that set the quality standard in a wide range of fluid handling solutions. Graco provides equipment for spray finishing, protective coating, paint circulation, lubrication, and dispensing sealants and adhesives, along with power application equipment for the contractor industry. Graco's ongoing investment in fluid management and control will continue to provide innovative solutions to a diverse global market.

GRACO LOCATIONS

MAILING ADDRESS

P.O. Box 1441
Minneapolis, MN 55440-1441
Tel: 612-623-6000
Fax: 612-623-6777

AMERICAS

MINNESOTA

Worldwide Headquarters
Graco Inc.
88-11th Avenue N.E.
Minneapolis, MN 55413

EUROPE

BELGIUM

European Headquarters
Graco N.V.
Industrieterrein-Oude Bunders
Slakweidestraat 31
3630 Maasmechelen,
Belgium
Tel: 32 89 770 700
Fax: 32 89 770 777

ASIA PACIFIC

AUSTRALIA

Graco Australia Pty Ltd.
Suite 17, 2 Enterprise Drive
Bundoora, Victoria 3083
Australia
Tel: 61 3 9468 8500
Fax: 61 3 9468 8599

CHINA

Graco Hong Kong Ltd.
Shanghai Representative Office
Room 118 1st Floor
No.2 Xin Yuan Building
No.509 Cao Bao Road
Shanghai, 200233
The People's Republic of China
Tel: 86 21 649 50088
Fax: 86 21 649 50077

INDIA

Graco Hong Kong Ltd.
India Liaison Office
Room 432, Augusta Point
Regus Business Centre 53
Golf Course Road
Gurgaon, Haryana
India 122001
Tel: 91 124 435 4208
Fax: 91 124 435 4001

JAPAN

Graco K.K.
1-27-12 Hayabuchi
Tsuzuki-ku
Yokohama City, Japan 2240025
Tel: 81 45 593 7300
Fax: 81 45 593 7301

KOREA

Graco Korea Inc.
Shinhan Bank Building
4th Floor #1599
Gwanyang-Dong, Dongan-Ku,
Anyang-si, Korea 431-060
Tel: 82 31 476 9400
Fax: 82 31 476 9801

SALES/ DISTRIBUTION/ SERVICE

Call today for product information or to talk with a Graco representative.

1-800-533-9655 or visit us at www.graco.com.

Graco Inc. is registered to I.S. EN ISO 9001

North America
Customer Service
800-533-9655
Fax 800-533-9656