

Adapter Fittings

Adapters - metric to inch/common inch pipe fittings



Male/Female Adapter ISO G (BSPP) to Inch

A male	B female	Per Pack*	Part No.
ISO G1/8	1/8" NPT	10	R432011744
ISO G1/4	1/4" NPT	10	R432011874
ISO G3/8	3/8" NPT	10	R432011847
ISO G1/2	1/2" NPT	10	R432011745
1/8" NPT	ISO G1/8	10	R432012022
1/4" NPT	ISO G1/4	10	R432012023
3/8" NPT	ISO G3/8	10	R432012024
1/2" NPT	ISO G1/2	10	R432012025



M7 Adapter fittings


Type	Part No.	Thread	Tube O.D.	Pack Qty.*
straight	1823373100	M7	4mm	25
straight	1823373088	M7	6mm	25
elbow	R412005377	M7	4mm	25
elbow	R412005378	M7	6mm	25
straight	R412004925	M7	1/8"	25
straight	R412004926	M7	1/4"	25



Hex Socket Pipe Plug

Size	A min/max (in.)	Part No.	Pack Qty.*
1/8" NPT	0.290/0.370	R432027753	1
1/4" NPT	0.417/0.475	R432027754	1
3/8" NPT	0.475/0.520	R432012266	1
1/2" NPT	0.524/0.630	R432027755	1


Material: Zinc plated steel



Hex Pipe Double Nipple

A	B (in.)	Hex Width (in.)	Part No.	Pack Qty.*
10-32 UNF	0.50	0.25	R432012043	1
1/8" NPT	0.97	0.44	R432012044	1
1/4" NPT	1.38	0.56	R432012041	1
3/8" NPT	1.41	0.69	R432030233	1
1/2" NPT	1.81	0.88	R432012042	1


Material: Brass



Reducer Bushing


A male	B female	C (in.)	Hex Width (in.)	New Part No.*	Pack Qty.*
1/8" NPT	10-32 UNF	0.53	0.44	R432030232	1
1/4" NPT	1/8" NPT	0.75	0.64	R432027750	1
3/8" NPT	1/8" NPT	0.75	0.68	R432012159	1
3/8" NPT	1/4" NPT	0.75	0.68	R432027749	1
1/2" NPT	1/4" NPT	1.00	0.88	R432027751	1
1/2" NPT	3/8" NPT	1.00	0.88	R432030225	1
3/4" NPT	1/4" NPT	1.00	1.12	R432030202	1
3/4" NPT	3/8" NPT	1.00	1.13	R432030201	1
3/4" NPT	1/2" NPT	1.06	1.13	R432012160	1

Material: Brass, except R432012160 is zinc plated steel.



Hybrid Fittings - Inch tube to Male BSPT (R ISO)

Part Number	ØD (in.)	C	F1 (in.)	F2 (in.)	H (in.)	K (in.)	wt. (oz.)
R432016913	5/32	R1/8	0.39	0.12	0.37	0.43	0.282
R432016914	1/8	R1/8	0.43	0.12	0.34	0.47	0.176
R432016917	1/4	R1/8	0.43	0.16	0.47	0.47	0.212
R432016918	1/4	R1/4	0.55	0.16	0.37	0.59	0.741
R432016919	3/8	R1/4	0.71	0.20	0.30	0.77	0.600
R432016922	1/2	R1/4	0.87	0.24	1.06	0.94	1.552
R432016920	3/8	R3/8	0.51	0.20	0.79	0.55	0.670
R432016923	1/2	R3/8	0.87	0.28	1.02	0.94	1.693
R432016921	3/8	R1/2	0.55	0.24	0.66	0.59	2.152
R432016924	1/2	R1/2	0.94	0.28	0.81	0.94	1.728



Note: BSP-T (R ISO tapered) threads can be used in an ISO G (BSPP) female port, with sealing ensured by thread sealant.

*Pack Quantity is order quantity multiple due to package size.